

ÖLFLEX® CLASSIC 110 BK

VDE-registered oil-resistant PVC control cable with black outer sheath for a wide range of applications

ÖLFLEX® CLASSIC 110 BK - PVC control cable, VDE registered, oil resistant, flexible and UV-resistant for various applications, 300/500V, also for YSLY or YY

Info

CPR: Article number choice under www.lappkabel.com/cpr

With black outer sheath, UV-resistant

VDE certificate of conformity with
factory surveillance



Good chemical resistance



Oil-resistant



Power chain



Torsion-resistant



UV-resistant

Benefits

Suitable for outdoor applications

Wide choice of standardized lengths and individual cuts

Application range

For fixed installation as well as occasional flexing at free, non-continuously recurring movement without tensile load

Dry or damp rooms that are subject to medium mechanical loads

Last Update (09.12.2022)

©2022 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

ÖLFLEX® CLASSIC 110 BK

Suitable for torsional applications which are typical for the loop in wind turbine generators (WTG)

In power chains for a travelling distance up to 5 m and 0,2 ... 1 million bending cycles, for following dimensions: 0,5 to 2.5mm² and 2 to 7 conductors

Suitable for outdoor applications

Product features

Flame-retardant according IEC 60332-1-2

Good chemical resistance, see catalogue appendix T1

Oil-resistant according to DIN EN 50290-2-22 (TM54)

UV and weather-resistant according to ISO 4892-2

Norm references / Approvals

VDE reg. no. 7030 for the following sizes:

up to 2.5 mm²: 2 - 65 cores

from 4 mm²: 2 - 7 cores

from 25 mm²: 2 - 5 cores

Product Make-up

Fine-wire strand made of bare copper wires

PVC insulation LAPP P8/1

Cores twisted in layers

PVC outer sheath, black (RAL 9005)

Technical Data

Classification ETIM 5:

ETIM 5.0 Class-ID: EC000104

ETIM 5.0 Class-Description: Control cable

Classification ETIM 6:

ETIM 6.0 Class-ID: EC000104

ETIM 6.0 Class-Description: Control cable

Core identification code:

Black with white numbers acc. to VDE 0293-334

Conductor stranding:

Fine wire according to DIN EN 60228 (VDE 0295), class 5 / IEC 60228 class 5

Torsion movement in WTG:

TW-0 & TW-1, refer to Appendix T0

Minimum bending radius:

Occasional flexing: 10 x outer diameter

In power chains: 15 x outer diameter

Fixed installation: 4 x outer diameter

Nominal voltage:

U0/U: 300/500 V

Test voltage:

4000 V

Protective conductor:

G = with GN-YE protective conductor

X = without protective conductor

Temperature range:

Occasional flexing: -15 °C to +70 °C

In power chains: -5 °C to +70 °C

Fixed installation: -40 °C to +80 °C

Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Last Update (09.12.2022)

©2022 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

ÖLFLEX® CLASSIC 110 BK

Packaging size: coil \leq 30 kg or \leq 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

ÖLFLEX® CLASSIC 110 BK

Article number	Number of cores and mm ² per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
1119809	2 X 0.75	5.4	14.4	45
1119871	3 G 0.75	5.7	21.6	55
1119892	3 X 0.75	5.7	21.6	55
1119872	4 G 0.75	6.2	28.8	66
1119893	4 X 0.75	6.2	28.8	66
1119873	5 G 0.75	6.7	36	79
1119874	7 G 0.75	7.3	50.4	101
1119875	12 G 0.75	9.9	86.4	171
1119876	18 G 0.75	11.7	130	244
1119877	25 G 0.75	13.8	180	337
1119878	34 G 0.75	15.9	245	448
1119894	2 X 1.0	5.7	19.2	53
1119244	3 G 1.0	6	28.8	65
1119895	3 X 1.0	6	28.8	65
1119245	4 G 1.0	6.5	38.4	79
1119896	4 X 1.0	6.5	38.4	79
1119246	5 G 1.0	7.1	48	94
1119897	5 X 1.0	7.1	48	94
1119247	7 G 1.0	8	67.2	126
1119248	12 G 1.0	10.5	115	205
1119249	18 G 1.0	12.7	173	290
1119251	25 G 1.0	14.7	240	390
1119252	34 G 1.0	17.1	326	551
1119898	2 X 1.5	6.3	28.8	68
1119020	3 G 1.5	6.7	43.2	84
1119899	3 X 1.5	6.7	43.2	84
1119879	4 G 1.5	7.2	57.6	104
1119900	4 X 1.5	7.2	57.6	104
1119880	5 G 1.5	8.1	72	128
1119911	5 X 1.5	8.1	72	128
1119881	7 G 1.5	8.9	101	166
1119913	7 X 1.5	8.9	101	166
1119882	12 G 1.5	12	173	279
1119883	18 G 1.5	14.4	259	407

Last Update (09.12.2022)

©2022 Lapp Group - Technical changes reserved

 Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03_16

ÖLFLEX® CLASSIC 110 BK

Article number	Number of cores and mm ² per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
1119884	25 G 1.5	16.9	360	560
1119914	2 X 2.5	7.5	48	100
1119885	3 G 2.5	8.1	72	132
1119886	4 G 2.5	8.9	96	163
1119887	5 G 2.5	10	120	200
1119888	7 G 2.5	11.1	168	267
1119889	12 G 2.5	14.8	288	444
1119890	18 G 2.5	17.8	432	648
1119891	25 G 2.5	20.8	600	890
1119915	3 G 4.0	9.9	115.2	201
1119916	4 G 4.0	10.8	154	249
1119917	5 G 4.0	12.1	192	315
1119918	4 G 6.0	13	230	365
1119919	5 G 6.0	14.5	288	447
1119920	4 G 10.0	16.2	384	590
1119921	5 G 10.0	18.1	480	722
1119922	4 G 16.0	18.8	614	1087
1119923	5 G 16.0	21.2	768	1370

Last Update (09.12.2022)

©2022 Lapp Group - Technical changes reserved

Product Management www.lappkabel.deYou can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03_16