

ÖLFLEX® PETRO C HFFR 0,6/1 kV

Chemically and mechanically robust cable for harsh environmental conditions - UL/cUL certified

ÖLFLEX® PETRO C HFFR - Screened power and control cable for oil-, mud- and abrasion resistant use in harsh offshore conditions with UL/cUL certification

Info

Resistant to oil and drilling fluids
according to NEK TS 606:2016 (Oil & Mud)
Highly flame retardant
UL/cUL certified for North America



Suitable for outdoor use



Flame-retardant



Halogen-free



Cold-resistant



Mechanical resistance



Oil-resistant



Interference signals



UV-resistant

Last Update (22.12.2023)

©2023 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

ÖLFLEX® PETRO C HFFR 0,6/1 kV

Benefits

Resistant to contact with many mineral oil-based lubricants, diluted acids, aqueous alkaline solutions and other chemical media
Reduced flame spreading increases the protection against damage to persons and property in the event of a fire
Wide temperature range for applications in harsh climatic environments
Copper braiding screens the cable against electromagnetic interference
Can be used in many applications from different industries due to its mechanical, thermal and chemical properties

Application range

Onshore and offshore applications
For electrical connection of drilling units, pumping stations, compressors or generators in harsh environmental conditions
Particularly in wet areas of machine tools and transfer lines
Chemical and petrochemical industry
For indoor and outdoor use

Product features

Resistant to oil and drilling fluids according to NEK TS 606:2016 and IEC 61892-4
Fire behaviour:
- Halogen-free according to VDE 0472-815
- Flame-retardant according to IEC 60332-1-2
- No flame propagation according to IEC 60332-3-22 cat. A
UV-resistant according to ISO 4892-2
Ozone-resistant according to EN 50396
Salt water-resistant according to UL 1309

Norm references / Approvals

Single-core versions:
USA: UL AWM Style 11624
Canada: cUL AWM II A/B
Multi-core versions:
USA: UL AWM Style 20234
Canada: cUL AWM II A/B

Product Make-up

Fine-wire, tinned-copper conductor
Core insulation: polyolefin compound
Cores twisted in layers
Inner sheath: halogen-free compound
Tinned copper screen braiding
Outer sheath made of robust special polymer, colour black

Technical Data

| | |
|---------------------------|--|
| Classification ETIM 5: | ETIM 5.0 Class-ID: EC000104 ETIM 5.0 Class-Description: Control cable |
| Classification ETIM 6: | ETIM 6.0 Class-ID: EC000104 ETIM 6.0 Class-Description: Control cable |
| Core identification code: | Colours according to VDE 0293-308, refer to Appendix T9 From 6 cores: black with white numbers |
| Fire test: | Flame-retardant acc. to IEC 60332-1-2, UL VW-1, Cable Flame Test, CSA FT 1 No flame-propagation according to IEC 60332-3-22 category A |

Last Update (22.12.2023)

©2023 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

ÖLFLEX® PETRO C HFFR 0,6/1 kV

| | |
|-------------------------|--|
| Conductor stranding: | Fine wire acc. to VDE 0295, class 5 / IEC 60228 class 5 from 0.5 mm ² |
| Minimum bending radius: | Occasional flexing: 20 x outer diameter Fixed installation: 6 x outer diameter |
| Nominal voltage: | IEC U0/U: 600/1000 V UL/CSA: 1000 V |
| Test voltage: | 4000 V |
| Temperature range: | Occasional flexing: -40 °C to +90 °C (UL/CSA: +80 °C) Fixed installation: -50 °C to +90 °C (UL/CSA: +80 °C) |

Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

ÖLFLEX® PETRO C HFFR 0,6/1 kV

| Article number | Number of cores and mm ² per conductor | Outer diameter [mm] | Copper index (kg/km) | Weight (kg/km) |
|--|---|---------------------|----------------------|----------------|
| ÖLFLEX® PETRO C HFFR black - single core | | | | |
| 0023249 | 1 X 70.0 | 19.3 | 737 | 948 |
| 0023250 | 1 X 95.0 | 21.6 | 1002 | 1155 |
| 0023251 | 1 X 120.0 | 24.5 | 1254 | 1463 |
| 0023248 | 1 X 150.0 | 26.1 | 1553 | 1767 |
| 0023233 | 1 X 185.0 | 28.4 | 1912 | 2349 |
| 0023234 | 1 X 240.0 | 32.6 | 2475 | 2869 |
| 0023279 | 1 X 300.0 | 34.7 | 3075 | 3817 |
| ÖLFLEX® PETRO C HFFR black - multi-core | | | | |
| 0023252 | 2 X 1.5 | 11.5 | 57 | 183 |
| 0023253 | 3 G 1.5 | 12 | 72 | 212 |
| 0023254 | 4 G 1.5 | 12.8 | 90 | 249 |
| 0023255 | 5 G 1.5 | 14 | 115 | 307 |
| 0023256 | 7 G 1.5 | 15.9 | 151 | 401 |
| 0023239 | 12 G 1.5 | 18.8 | 238 | 573 |
| 0023257 | 18 G 1.5 | 22.3 | 350 | 846 |
| 0023240 | 25 G 1.5 | 26.6 | 490 | 1183 |
| 0023278 | 3 G 2.5 | 13.5 | 105 | 276 |
| 0023242 | 4 G 2.5 | 14.6 | 147 | 347 |
| 0023244 | 5 G 2.5 | 15.7 | 171 | 401 |
| 0023245 | 7 G 2.5 | 18.3 | 233 | 547 |
| 0023258 | 12 G 2.5 | 22.3 | 378 | 840 |
| 0023260 | 4 G 4.0 | 16.2 | 212 | 457 |
| 0023266 | 5 G 4.0 | 17.6 | 250 | 540 |
| 0023261 | 4 G 6.0 | 17.7 | 288 | 558 |
| 0023268 | 5 G 6.0 | 19.9 | 367 | 710 |
| 0023280 | 4 G 10.0 | 22.3 | 474 | 882 |
| 0023272 | 5 G 10.0 | 24.3 | 582 | 1069 |
| 0023281 | 4 G 16.0 | 24.9 | 716 | 1208 |
| 0023269 | 5 G 16.0 | 27.6 | 881 | 1483 |
| 0023267 | 4 G 25.0 | 30.2 | 1096 | 1785 |
| 0023270 | 5 G 25.0 | 33.4 | 1371 | 2206 |
| 0023262 | 4 G 35.0 | 33.6 | 1515 | 2314 |
| 0023282 | 5 G 35.0 | 37.1 | 1,921.3 | 2847 |

Last Update (22.12.2023)

©2023 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03_16

ÖLFLEX® PETRO C HFFR 0,6/1 kV

| Article number | Number of cores and mm ² per conductor | Outer diameter [mm] | Copper index (kg/km) | Weight (kg/km) |
|--|---|---------------------|----------------------|----------------|
| 0023246 | 4 G 50.0 | 39.3 | 2140 | 3264 |
| 0023271 | 5 G 50.0 | 43.4 | 2620 | 4002 |
| ÖLFLEX® PETRO C HFFR blue - multi-core | | | | |
| 0023263 | 2 X 1.5 | 11.5 | 57 | 183 |
| 0023283 | 3 G 1.5 | 12 | 72 | 212 |
| 0023237 | 4 G 1.5 | 12.8 | 90 | 249 |
| 0023284 | 5 G 1.5 | 14 | 115 | 307 |
| 0023238 | 7 G 1.5 | 15.9 | 151 | 401 |
| 0023264 | 12 G 1.5 | 18.8 | 238 | 573 |
| 0023265 | 25 G 1.5 | 26.6 | 490 | 1183 |

Last Update (22.12.2023)

©2023 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03_16