

ÖLFLEX® SERVO 9YSLCY-JB

EMC-optimised motor cable, low-capacitance, double-screened, certified

ÖLFLEX® SERVO 9YSLCY-JB - double screened power cable for large servo drive systems with high electrical load, UL/cUL certified

Info

AWM certification for USA and Canada

3+3 symmetry reduces common-mode interference effects and bearing currents

CPR: Article number choice under www.lappkabel.com/cpr



Interference signals

Benefits

EMC-compliant operation of power drive systems

High power transmission for large drives

Low capacitance design enables longer cable connection between frequency converter and motor

Symmetrical 3+3 Version supports the reduction of damaging bearing currents

Versions with black outer sheath are suitable for outdoor use

Application range

Connecting cable between frequency converter and motor

In dry, damp or wet interiors

Paper industry

Chemical industry

Heavy industry

Product features

Flame-retardant according to IEC 60332-1-2 & CSA FT1

EN/VDE +90° C PP insulation

Norm references / Approvals

Last Update (21.12.2023)

©2023 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

ÖLFLEX® SERVO 9YSLCY-JB

USA: AWM Style 2570 or 20886, 1kV 80°C VW-1
Canada: AWM I/II A/B 1kV 80°C FT1
UL File No. E63634
Based on VDE 0276, 0250, 0207

Product Make-up

Fine-wire, bare copper conductor
Core insulation: polypropylene (PP)
Cores twisted concentrically (symmetrically splitted protective conductor of 3+3 version is gusset-filling divided between the power cores)
Screening: wrapping of laminated aluminium foil in combination with tinned copper braiding
4-core design: transparent PVC outer sheath
3+3 core version: PVC outer sheath, black

Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC000057 ETIM 5.0 Class-Description: Low voltage power cable
Classification ETIM 6:	ETIM 6.0 Class-ID: EC000057 ETIM 6.0 Class-Description: Low voltage power cable
Core identification code:	Colours according to HD 308 S2 VDE 0293-308
Conductor stranding:	Fine wire according to VDE 0295 Class 5/ IEC 60228 Class 5
Minimum bending radius:	Occasional flexing: 15 x outer diameter Fixed installation: 4 x outer diameter
Nominal voltage:	IEC U0/U: 600/1000 V UL & CSA: 1000 V
Test voltage:	4000 V
Protective conductor:	Protective conductor of 3+3 version is gusset-filling divided between power cores
Temperature range:	Flexing: IEC: transparent -5°C to +80°C IEC: black -5°C to +90°C UL/CSA: -5°C to +80°C Fixed installation: IEC: transparent -40°C to +80°C IEC: black -40°C to +90°C UL/CSA: +80°C

Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

ÖLFLEX® SERVO 9YSLCY-JB

Article number	Number of cores and mm ² per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® SERVO 9YSLCY-JB / 4-core version - transparent outer sheath				
0037000	4 G 1,5	10.5	87	230
0037001	4 G 2,5	11.8	133	300
0037002	4 G 4	13.3	213	485
0037003	4 G 6	14.9	298	630
0037004	4 G 10	17.7	460	860
0037005	4 G 16	21.5	707	1290
0037006	4 G 25	26.3	1100	1860
0037007	4 G 35	29.7	1542	2610
0037008	4 G 50	35.8	2206	2950
0037009	4 G 70	40.9	3002	3950
0037010	4 G 95	45.4	4004	5300
0037011	4 G 120	49.8	5108	6600
0037012	4 G 150	56.1	6225	7590
0037013	4 G 185	61.4	7568	9420
0037014	4 G 240	67.9	9940	12150
ÖLFLEX® SERVO 9YSLCY-JB / 3+3 core version - black outer sheath				
0037015	3 X 1,5 + 3 G 0,25	11.4	88	177
0037016	3 X 2,5 + 3 G 0,5	12.9	130	220
0037017	3 X 4 + 3 G 0,75	13.6	224	323
0037018	3 X 6 + 3 G 1,0	15.2	276	420
0037019	3 X 10 + 3 G 1,5	17.4	511	635
0037020	3 X 16 + 3 G 2,5	20	751	930
0037021	3 X 25 + 3 G 4	24.3	1204	1350
0037022	3 X 35 + 3 G 6	27.5	1535	1780
0037023	3 X 50 + 3 G 10	31.1	2156	2530
0037024	3 X 70 + 3 G 10	37.1	2980	3225
0037025	3 X 95 + 3 G 16	40	3953	4511
0037026	3 X 120 + 3 G 16	42.6	4836	5663
0037027	3 X 150 + 3 G 25	50	5412	6720
0037028	3 X 185 + 3 G 35	55.6	7077	7855

Last Update (21.12.2023)

©2023 Lapp Group - Technical changes reserved

 Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03_16