

SKINDICHT® BL-M

SKINDICHT® BL-M, brass blind plugs for closing pre-threaded holes, assembling with screwdriver



Corrosion-resistant



Robust



Reliability



Temperature-resistant

Benefits

Withstands temperatures up to +200 °C.

Simple assembly by using a slotted screwdriver.

Article numbers ending in "LF" are lead-free product alternatives with the same product properties. "Lead-free" articles do not contain lead, which is currently still allowed to make up to four percent in copper alloys. It could be banned in the future according to the RoHS Directive.

Application range

For closing an unoccupied metric threaded hole on the housing.

Withstands high chemical and mechanical stress.

Product features

Assembling with screwdriver

Norm references / Approvals

UL File Nr. E79903

Product Make-up

Last Update (22.12.2023)

©2023 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

SKINDICHT® BL-M

Metric connection thread acc. to DIN EN 60423
Basis for technical information DIN IEC 62444

Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC000032 ETIM 5.0 Class-Description: Plug for cable screw gland
Classification ETIM 6:	ETIM 6.0 Class-ID: EC000032 ETIM 6.0 Class-Description: Plug for cable screw gland
Certifications:	UL File E79903
On request:	Fitted with FKM O-ring (-20 °C to +200 °C)
Material:	Body: nickel-plated brass O-ring: NBR
Protection rating:	IP 54 IP 68 (with O-ring)
Temperature range:	With O-ring: -20 °C to +100 °C Without O-ring: -60 °C to +200 °C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

SKINDICHT® BL-M

Article number	Article designation / size	Overall length C mm	Thread length D mm	Outer Ø (mm)	Pieces / PU
SKINDICHT® BL-M					
52103100	M 12 x 1,5	7.5	5	14.0	100
52103110	M 16 x 1,5	8.0	5	18.0	100
52103120	M 20 x 1,5	9.5	6	22.0	100
52103130	M 25 x 1,5	11.0	7	28.0	100
52103140	M 32 x 1,5	12.0	8	35.0	50
52103150	M 40 x 1,5	13.0	9	44.0	25
52103160	M 50 x 1,5	15.0	9	54.0	10
52103170	M 63 x 1,5	16.0	10	70.0	10
52103190	M 75 x 1,5	17.0	11	80.0	1
52103100LF	M 12 x 1,5	7.5	5	14.0	100
52103110LF	M 16 x 1,5	8.0	5	18.0	100
52103120LF	M 20 x 1,5	9.5	6	22.0	100
52103130LF	M 25 x 1,5	11.0	7	28.0	100
52103140LF	M 32 x 1,5	12.0	8	35.0	50
52103150LF	M 40 x 1,5	13.0	9	44.0	25
52103160LF	M50x1,5	15.0	9	54.0	10
52103170LF	M63x1,5	16.0	10	70.0	10
52103190LF	M75x1,5	17.0	11	80.0	1
SKINDICHT® BL-M with O-ring					
52103105	M 12 x 1,5	7.5	5	14.0	100
52103115	M 16 x 1,5	8.0	5	18.0	100
52103125	M 20 x 1,5	9.5	6	22.0	100
52103135	M 25 x 1,5	11.0	7	28.0	100
52103145	M 32 x 1,5	12.0	8	35.0	50
52103155	M 40 x 1,5	13.0	9	44.0	25
52103165	M 50 x 1,5	15.0	9	54.0	10
52103175	M 63 x 1,5	16.0	10	70.0	10
52103105LF	M 12 x 1,5	7.5	5	14.0	100
52103115LF	M 16 x 1,5	8.0	5	18.0	100
52103125LF	M 20 x 1,5	9.5	6	22.0	100
52103135LF	M 25 x 1,5	11.0	7	28.0	100
52103145LF	M 32 x 1,5	12.0	8	35.0	50
52103155LF	M 40 x 1,5	13.0	9	44.0	25
52103175LF	M63x1,5	16.0	10	70.0	10

Last Update (22.12.2023)

©2023 Lapp Group - Technical changes reserved

 Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03_16

SKINDICHT® BL-M

Article number	Article designation / size	Overall length C mm	Thread length D mm	Outer Ø (mm)	Pieces / PU
52103195LF	M75x1,5	17.0	11	80.0	1

Last Update (22.12.2023)

©2023 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

SKINDICHT® BL-M

